INDIAN SCHOOL AL WADI AL KABIR

DEPARTMENT OF COMPUTER SCIENCE

HTML Tags Chart

Tag	Name	Code Example	Browser View
<!--	**comment**	**<!--**This can be viewed in the **HTML** part of a document**-->**	Nothing will show (Tip)
<a -	**anchor**	** Visit Our Site****	Visit Our Site (Tip)
	bold	****Example****	**Example**
<big>	**big (text)**	**<big>**Example**</big>**	Example (Tip)
<body>	**body of HTML document**	**<body>**The content of your **HTML** page**</body>**	Contents of your web page (Tip)
 	line break	The contents of your page** **The contents of your page	The contents of your web page The contents of your web page
	center	** **This will center your contents** **	This will center your contents
<dd>	**definition description**	<dl> <dt>Definition Term</dt> **<dd>Definition of the term</dd>** <dt>Definition Term</dt> **<dd>Definition of the term</dd>** </dl>	Definition Term **Definition of the term** Definition Term **Definition of the term**
<dl>	**definition list**	**<dl>** <dt>Definition Term</dt> <dd>Definition of the term</dd> <dt>Definition Term</dt> <dd>Definition of the term</dd> **</dl>**	Definition Term Definition of the term Definition Term Definition of the term
<dt>	**definition term**	<dl> **<dt>Definition Term</dt>** <dd>Definition of the term</dd> **<dt>Definition Term</dt>** <dd>Definition of the term</dd> </dl>	**Definition Term** Definition of the term **Definition Term** Definition of the term
	emphasis	This is an ****Example**** of using the emphasis tag	This is an *Example* of using the emphasis tag
<embed>	**embed object**	**<embed** src="yourfile.mid" width="100%" height="60" align="center">	(Tip)
<embed>	**embed object**	<**embed** src="yourfile.mid" autostart="true" hidden="false" loop="false"> <noembed><bgsound src="yourfile.mid" loop="1"></noembed>	Music will begin playing when your page is loaded and will only play one time. A control panel will be displayed to enable your visitors to stop the music.
	font	**<font** face="Times New Roman">Example****	Example (Tip)

	font	**<font** face="Times New Roman" size="4">Example****	Example (Tip)
	font	**<font** face="Times New Roman" size="+3" color="#ff0000">Example****	Example (Tip)
<form>	**form**	**<form** action="mailto:you@yourdomain.com "> Name: <input name="Name" value="" size="10"> Email: <input name="Email" value="" size="10"> <input type="submit"> **</form>**	Name: (Tip) Email: Submit
<h1> <h2> <h3> <h4> <h5> <h6>	**heading 1** **heading 2** **heading 3** **heading 4** **heading 5** **heading 6**	** **Heading 1 Example** ** ** **Heading 2 Example** ** ** **Heading 3 Example** ** ** **Heading 4 Example** ** ** **Heading 5 Example** ** ** **Heading 6 Example** **	Heading 1 Heading 2 Heading 3 Heading 4 Heading 5 Heading 6
<head>	**heading of HTML document**	**<head>**Contains elements describing the document**</head>**	Nothing will show
<hr>	**horizontal rule**	**<hr />**	Contents of your web page (Tip) Contents of your web page
<hr>	**horizontal rule**	**<hr** width="50%" size="3" />	Contents of your web page Contents of your web page
<hr>	**horizontal rule**	**<hr** width="50%" size="3" noshade />	Contents of your web page Contents of your web page
<hr> (Internet Explorer)	**horizontal rule**	**<hr** width="75%" color="#ff0000" size="4" />	Contents of your web page Contents of your web page
<hr> (Internet Explorer)	**horizontal rule**	**<hr** width="25%" color="#6699ff" size="6" />	Contents of your web page Contents of your web page
<html>	**hypertext markup language**	**<html>** <head> <meta> <title>Title of your web page</title> </head> <body>**HTML web page** contents </body> **</html>**	Contents of your web page
	italic	****Example****	*Example*
<img>	**image**	**<img** src="Earth.gif" width="41" height="41" border="0" alt="text describing the image" />	(Tip)

<input>	**input field**	Example 1: <form method=post action="/cgi-bin/example.cgi"> **<input** type="text" size="10" maxlength="30"> **<input** type="Submit" value="Submit"> </form>	Example 1: (Tip)
<input> (Internet Explorer)	**input field**	Example 2: <form method=post action="/cgi-bin/example.cgi"> **<input** type="text" style="color: #ffffff; font-family: Verdana; font-weight: bold; font-size: 12px; background-color: #72a4d2;" size="10" maxlength="30"> **<input** type="Submit" value="Submit"> </form>	Example 2: (Tip)
<input>	**input field**	Example 3: <form method=post action="/cgi-bin/example.cgi"> <table border="0" cellspacing="0" cellpadding="2"><tr><td bgcolor="#8463ff"><input type="text" size="10" maxlength="30"></td><td bgcolor="#8463ff" valign="Middle"> <input type="image" name="submit" src="yourimage.gif"></td></tr> </table> </form>	Example 3: (Tip)
<input>	**input field**	Example 4: <form method=post action="/cgi-bin/example.cgi"> Enter Your Comments: <textarea wrap="virtual" name="Comments" rows=3 cols=20 maxlength=100></textarea> **<input** type="Submit" value="Submit"> **<input** type="Reset" value="Clear"> </form>	Example 4: (Tip)
<input>	**input field**	Example 5: <form method=post action="/cgi-bin/example.cgi"> Select an option: <select> <option >option 1</option> <option selected>option 2</option> <option>option 3</option> <option>option 4</option> <option>option 5</option> <option>option 6</option> </select> **<input** type="Submit" value="Submit"> </form>	Example 5: Tip) 
<input>	**input field**	Example 6:	Example 6: (Tip)

		<form method=post action="/cgi-bin/example.cgi"> Select an option: **<input** type="radio" name="option"> Option 1 **<input** type="radio" name="option" checked> Option 2 **<input** type="radio" name="option"> Option 3 Select an option: **<input** type="checkbox" name="selection"> Selection 1 **<input** type="checkbox" name="selection" checked> Selection 2 **<input** type="checkbox" name="selection"> Selection 3 **<input** type="Submit" value="Submit"> </form>	Select an option: Option 1 Option 2 Option 3 Select an option: Selection 1 Selection 2 Selection 3 Submit
	list item	Example 1: <menu> **<li** type="disc">List item 1** ** **<li** type="circle">List item 2** ** **<li** type="square">List item 3** ** </MENU> Example 2: <ol type="i"> ** **List item 1** ** ** **List item 2** ** ** **List item 3** ** ** **List item 4** ** 	Example 1: (Tip) • **List item 1** o **List item 2** ▪ **List item 3** Example 2: i. **List item 1** ii. **List item 2** iii. **List item 3** iv. **List item 4**
<link>	**link**	<head> <link rel="stylesheet" type="text/css" href="style.css" /> </head>	
<marquee> (Internet Explorer)	**scrolling text**	**<marquee** bgcolor="#cccccc" loop="-1" scrollamount="2" width="100%">Example Marquee**</marquee>**	(Tip)
<menu>	**menu**	**<menu>** <li type="disc">List item 1 <li type="circle">List item 2 <li type="square">List item 3 **</menu>**	• List item 1 o List item 2 ▪ List item 3
<meta>	**meta**	**<meta** name="Description" content="Description of your site"> **<meta** name="keywords" content="keywords describing your site">	Nothing will show (Tip)
<meta>	**meta**	**<meta** HTTP-EQUIV="Refresh" CONTENT="4;URL=http://www.yourdomain.com/">	Nothing will show (Tip)

<meta>	**meta**	**<meta** http-equiv="Pragma" content="no-cache">	Nothing will show (Tip)
<meta>	**meta**	**<meta** name="rating" content="General">	Nothing will show (Tip)
<meta>	**meta**	**<meta** name="robots" content="all">	Nothing will show (Tip)
<meta>	**meta**	**<meta** name="robots" content="noindex,follow">	Nothing will show (Tip)
	ordered list	**Numbered** ** ** - List item 1 - List item 2 - List item 3 - List item 4 ** ** **Numbered Special Start** **<ol start="5">** - List item 1 - List item 2 - List item 3 - List item 4 ** ** **Lowercase Letters** **<ol type="a">** - List item 1 - List item 2 - List item 3 - List item 4 ** ** **Capital Letters** **<ol type="A">** - List item 1 - List item 2 - List item 3 - List item 4 ** ** **Capital Letters Special Start** **<ol type="A" start="3">** - List item 1 - List item 2 - List item 3 - List item 4 ** ** **Lowercase Roman Numerals** **<ol type="i">** - List item 1 - List item 2 - List item 3 - List item 4 ** **	**Numbered** 1. List item 1 2. List item 2 3. List item 3 4. List item 4 **Numbered Special Start** 5. List item 1 6. List item 2 7. List item 3 8. List item 4 **Lowercase Letters** a. List item 1 b. List item 2 c. List item 3 d. List item 4 **Capital Letters** A. List item 1 B. List item 2 C. List item 3 D. List item 4 **Capital Letters Special Start** C. List item 1 D. List item 2 E. List item 3 F. List item 4 **Lowercase Roman Numerals** i. List item 1 ii. List item 2 iii. List item 3 iv. List item 4 **Capital Roman Numerals** I. List item 1 II. List item 2 III. List item 3 IV. List item 4

		Capital Roman Numerals **<ol type="I">** - List item 1 - List item 2 - List item 3 - List item 4 ** ** **Capital Roman Numerals Special Start** **<ol type="I" start="7">** - List item 1 - List item 2 - List item 3 - List item 4 ** **	**Capital Roman Numerals Special Start** VII. List item 1 VIII. List item 2 IX. List item 3 X. List item 4
<option>	**listbox option**	<form method=post action="/cgi-bin/example.cgi"> Select an option: <select> **<option>**option 1**</option>** **<option selected>**option 2**</option>** **<option>**option 3**</option>** **<option>**option 4**</option>** **<option>**option 5**</option>** **<option>**option 6**</option>** </select> </form>	Select an option: (Tip) option 2
<p>	**paragraph**	This is an example displaying the use of the paragraph tag. <p> This will create a line break and a space between lines. Attributes: Example 1: **<p align="left">** This is an example displaying the use of the paragraph tag. Example 2: **<p align="right">** This is an example displaying the use of the paragraph tag. Example 3: **<p align="center">** This is an example displaying the use of the paragraph tag.	This is an example displaying the use of the paragraph tag. This will create a line break and a space between lines. Attributes: Example 1: This is an example displaying the use of the paragraph tag. Example 2: This is an example displaying the use of the paragraph tag. Example 3: This is an example displaying the use of the paragraph tag.
<small>	**small (text)**	****Example****	Example (Tip)

<table>
<tr><td><strike></td><td>deleted text</td><td><strike>Example</strike></td><td><s>Example</s></td></tr>
<tr><td></td><td>strong emphasis</td><td>Example</td><td>Example</td></tr>
<tr><td><table></td><td>table</td><td>Example 1:

<table border="4" cellpadding="2" cellspacing="2" width="100%">
<tr>
<td>Column 1</td>
<td>Column 2</td>
</tr>
</table>

Example 2: (Internet Explorer)

<table border="2" bordercolor="#336699" cellpadding="2" cellspacing="2" width="100%">
<tr>
<td>Column 1</td>
<td>Column 2</td>
</tr>
</table>

Example 3:

<table cellpadding="2" cellspacing="2" width="100%">
<tr>
<td bgcolor="#cccccc">Column 1</td>
<td bgcolor="#cccccc">Column 2</td>
</tr>
<tr>
<td>Row 2</td>
<td>Row 2</td>
</tr>
</table></td><td>Example 1: (Tip)
<table><tr><td>Column 1</td><td>Column 2</td></tr></table>
Example 2: (Tip)
<table><tr><td>Column 1</td><td>Column 2</td></tr></table>
Example 3: (Tip)
<table><tr><td>Column 1</td><td>Column 2</td></tr><tr><td>Row 2</td><td>Row 2</td></tr></table></td></tr>
<tr><td><td></td><td><table border="2" cellpadding="2" cellspacing="2" width="100%">
<tr>
<td>Column 1</td>
<td>Column 2</td>
</tr>
</table></td><td><table><tr><td>Column 1</td><td>Column 2</td></tr></table></td></tr>
<tr><td><th></td><td>table header</td><td>
<table>
<tr>
<th>Column 1</th>
<th>Column 2</th>
<th>Column 3</th>
</tr>
<tr>
<td>Row 2</td>
<td>Row 2</td>
<td>Row 2</td>
</tr>
<tr>
<td>Row 3</td>
<td>Row 3</td>
<td>Row 3</td>
</tr></td><td><table><tr><th>Column 1</th><th>Column 2</th><th>Column 3</th></tr><tr><td>Row 2</td><td>Row 2</td><td>Row 2</td></tr><tr><td>Row 3</td><td>Row 3</td><td>Row 3</td></tr><tr><td>Row 4</td><td>Row 4</td><td>Row 4</td></tr></table></td></tr>
</table>

		</tr> <tr> <td>Row 4</td> <td>Row 4</td> <td>Row 4</td> </tr> </table> 	
<title>	**document title**	**<title>**Title of your **HTML page</title>**	Title of your web page will be viewable in the title bar.(Tip)
<tr>	**table row**	<table border="2" cellpadding="2" cellspacing="2" width="100%"> **<tr>** <td>Column 1</td> <td>Column 2</td> **</tr>** </table>	**Column 1** **Column 2**
<tt>	**teletype**	**<tt>**Example**</tt>**	Example
<u>	**underline**	<u>Example</u>	Example
	unordered list	Example 1: ** ** - List item 1 - List item 2 ** ** Example 2: **<ul type="disc">** - List item 1 - List item 2 **<ul type="circle">** - List item 3 - List item 4 ** ** ** **	Example 1: • List item 1 • List item 2 Example 2: • List item 1 • List item 2 o List item 3 o List item 4